



SAFE & VAULT MANUFACTURERS

# PREMIER HIGH SECURITY SAFE

TDR TORCH & DRILL RESISTING

EQUIVALENT TO  USA: UL TRTL-60  EU: ABIS GRADE 4



MODEL PR3



**TDR torch and drill resisting**



Premier High Security Safe TDR suggested insurable cash rating in unsupported (no alarms) situation is **\$250,000**.



Premier High Security Safe TDR designed to be **fire resisting for one hour**



**MADE IN AUSTRALIA**



SAFE & VAULT MANUFACTURERS

# PREMIER HIGH SECURITY SAFE

TDR TORCH & DRILL RESISTING

EQUIVALENT TO USA: UL TRTL-60 EU: ABIS GRADE 4

**BODY:** The body gives a minimum thickness of 80mm of high density refractory materials at all points. These materials are bonded between inner and outer walls of specially reinforced steel, becoming a complete monolith after pouring. The engagement of the door and body effectively result in a continuous cube of exceptional strength and security.

**DOOR:** The door of the Premier safe has an overall thickness of 135mm, and the 55mm thick defensive slab section contains metals highly resistant to drills and abrasive grinders in addition to the high strength poured barrier materials and other defences. The lockcase forms an integral part of the entire door structure, giving additional strength.

**BOLTWORK:** Heavy 32mm bolts provide 4 way locking into reinforced sections of the 2 sides, top and bottom of the safe body.

**MOUNTING:** 2 x 20mm recessed bolt holes in base of safe.

**HINGING:** Fully adjustable antijacking hinges, available in standard right hand or optional left hand hinging.

**SHELVING:** All models come standard with 2 x adjustable shelves.

**RE-LOCKER:** Glass operated re-locker.

**LOCKS:** All models available with key, dial combination or digital locking at no extra cost.



MODEL PR3  
Drawer unit optional extra

## RESISTING TO

- Oxy-Acetylene attack
- Explosives and force
- Drills and abrasive grinders
- Pneumatic tools
- Hydraulic tools

Model	Height mm		Width mm		Depth mm		Weight	Litres	Locking Points
	External	Internal	External	Internal	External	Internal			
<b>PRA</b>	510	355	435	280	435	225	210kg	22	4
<b>PRB</b>	615	460	460	300	510	285	308kg	39	4
<b>PR1</b>	660	508	560	405	560	330	372kg	68	8
<b>PR2</b>	770	610	610	460	660	435	500kg	120	8
<b>PR3</b>	915	762	610	460	660	435	568kg	150	8
<b>PR4</b>	1070	910	660	508	660	435	704kg	195	10
<b>PR5</b>	1070	910	765	610	850	585	926kg	321	10
<b>PR6</b>	1220	1065	765	610	850	585	1026kg	375	10
<b>PR7</b>	1370	1219	765	610	850	585	1128kg	428	12
<b>PR8</b>	1525	1372	765	610	850	585	1230kg	484	12
<b>PR9</b>	1675	1524	765	610	850	585	1345kg	537	12
<b>PR10</b>	1835	1678	765	610	850	585	1464kg	590	12

### IMPORTANT

Allow 55mm projection for handle on depth measurement.



**ALL CMI SAFES COME WITH A FIVE YEAR WARRANTY, EXCLUDING FREIGHT AND TRAVELLING, WITH A 24 MONTH WARRANTY ON LOCKS.**



Supplied & Expertly Installed By:



1300 764 971  
www.safeguardsales.com.au