



CL410-CL460 safety cabinets Combi-Line

- Type tested and supervised security by ECB-S/Vds
- BURG-WÄCHTER safety cabinets with a certification which is valid all over Europe. For the safe storage of documents, cash, jewellery, arms or ammunition, coins and valuables.
- New pad design
- Admin & User code
- Time Date Year
- Audit trail
- Security Level S 2 according to DIN EN 14450
- Security Level B according to VDMA 24992. May 1995
 Fire resistance LFS 30 P according to EN 15659 30
 minutes fire protection for paper
- Fire-protective material according to DIN 4102

- Composite insulation in front of the door leaf provides heat protection for the lock and bolts
- Tested and certified protection against burglary and fire
- Double-walled construction
- Internal hinge Lateral locking through 25mm diameter strong round bolts plus sliding bolt on the top
- All-over gripping rail on the hinge side
- Prepared for both wall and floor fixing, 2 diagonally arranged drill holes on the back wall and 2 on the bottom
- Fixings included
- Colour: Black
- Keyed model (S) supplied with 2 keys
- Comes with 1 shelf each as standard

Version - S (Keyed)

Article	Exterior H x W x D	Interior H x W x D	Door H x W	Weight (kg)	Volume (I)
CL 410 K	320 x 435 x 380	205 x 320 x 232	205 x 265	44,0	15,0
CL 420 K	360 x 495 x 445	245 x 380 x 297	245 x 325	55,0	27,0
CL 440 K	560 x 495 x 445	445 x 380 x 297	445 x 325	77,0	50,0
CL 460 K	820 x 495 x 445	694 x 380 x 297	694 x 324	111,0	78,0



Security safe lock "SecuSafe', Vds tested, ECB.S certified according to EN 1300 class A, 9 levers, more than 1.000.000 key differs.

Version - E (Electronic)

Article	Exterior H x W x D	Interior H x W x D	Door H x W	Weight (kg)	Volume (I)
CL 410 E	320 x 435 x 380	205 x 320 x 232	205 x 265	44,0	15,0
CL 420 E	360 x 495 x 445	245 x 380 x 297	245 x 325	55,0	27,0
CL 440 E	560 x 495 x 445	445 x 380 x 297	445 x 325	77,0	50,0
CL 460 E	820 x 495 x 445	694 x 380 x 297	694 x 324	111,0	78,0



Electronic combination lock SecuTronic, Vds tested, ECB-S certified according to B/EN 1300 class B, 1.000.000 different combinations possible, incl. 3 batteries, type Micro LR 03 AAA. The locking armature protrudes 7 mm.



